


# BWT besthead FLEX

## Filter head for all filter cartridges from BWT water+more


### The new filter head with universal connection

The new BWT besthead FLEX filter head fits every BWT water+more filter cartridge, ensuring perfect flow to the filter and making water optimisation at the point of use even easier, safer and more convenient. The **user-friendly handling** during venting is the most convenient on the market, while the blend setting with lock function is extremely safe. The **FLEX Insert connections** with 30° lock are a real blessing for users and operators, enabling connection to the mains water supply and the consumer without the need for tools. An extensive range of accessories for the FLEX Insert and attachment parts in various shapes and sizes allow safe, kink-free lines and optimum economy when space is at a premium in vending machines and under the counter.

The BWT besthead FLEX filter heads are made from **food-safe materials**. Two DVGW-compliant one-way valves prevent water from flowing back into the mains or the filter cartridge and protect against uncontrolled water leakage. The BWT besthead FLEX filter heads are pressure resistant and safe. They can be used in any mains water system worldwide.




**FLEX Socket**  
 – With 30° lock for angled outlet  
 – Anti-twist tooth system



**FLEX Insert Connector**  
 – Easy insertion  
 – For all installation situations

**EASY Bypass blend setting**  
 – Secure locking  
 – Easy-to-see blend setting

Press and turn to adjust



**EASY Vent venting valve**  
 – Safe and easy handling  
 – Reliable venting

Retaining clip

Connector 90° ellbow, FLEX Insert made from GFP

Socket for retaining bracket

Venting hose

Outlet: optimised water for consumers such as coffee machines etc.

Raw water entry

Filter cartridge

## BWT besthead FLEX with wide range of FLEX Insert connectors



## Technical data

BWT besthead FLEX	
Inlet pressure	2–8 bar
Water temperature	4–30 °C
Ambient temperature	4–40 °C



30° lock adjustment for efficient installation of 90° elbows

## Delivery form

Order number

BWT besthead FLEX with 2 connectors 90° ellbow, FLEX Insert, M 3/8"	FS00Z20A00
---	------------

## Accessories

<b>Connector straight</b>	
Connector straight, FLEX Insert x M 3/8" made from GFP	FS00Z21A00
Connector straight, FLEX Insert x M 1/2" made from GFP	FS00Z22A00
Connector straight, FLEX Insert x M 3/4" made from GFP	FS00Z23A00
Connector straight, FLEX Insert x John Guest plug-in connector Ø 8 mm made from GFP	FS00Z24A00
Connector straight, FLEX Insert x John Guest plug-in connector Ø 3/8" made from GFP	FS00Z25A00
<b>Connector 90° ellbow</b>	
Connector 90° ellbow, FLEX Insert x M 3/8" made from GFP	FS00Z26A00
Connector 90° ellbow, FLEX Insert x M 1/2" made from GFP	FS00Z27A00
Connector 90° ellbow, FLEX Insert x M 3/4" made from GFP	FS00Z28A00
Connector 90° ellbow, FLEX Insert x John Guest plug-in connector Ø 8 mm made from GFP	FS00Z29A00
<b>Connector</b>	
Connector, double nipple, 2 x FLEX Insert made from GFP	FS00Z30A00
<b>Connection hose, straight connection</b>	
Connection hose DN 8, 1.5 m, FLEX Insert straight made from GFP, cap nut FM 3/8"	FS00Z36A00
Connection hose DN 8, 1.5 m, FLEX Insert straight made from GFP, cap nut FM 1/2"	FS00Z37A00
Connection hose DN 8, 1.5 m, FLEX Insert straight made from GFP, cap nut FM 3/4"	FS00Z38A00
<b>Connection hose, ellbow connection</b>	
Connection hose DN 8, 1.5 m, FLEX Insert 90° ellbow made from GFP, cap nut FM 3/8"	FS00Z32A00
Connection hose DN 8, 1.5 m, FLEX Insert 90° ellbow made from GFP, cap nut FM 1/2"	FS00Z33A00
Connection hose DN 8, 1.5 m, FLEX Insert 90° ellbow made from GFP, cap nut FM 3/4"	FS00Z34A00
Connection hose DN 8, 1.5 m, with ball valve, FLEX Insert 90° ellbow made from GFP, cap nut FM 3/8"	FS00Z35A00
<b>Brackets</b>	
Retaining bracket for under-table installation	FS00Y66A00
Retaining bracket extension for filter cartridges size 2XL wall installation	FS00Y73A00
<b>BWT besthead FLEX – Set 1</b>	
– BWT besthead FLEX with 2 connectors 90° ellbow, FLEX Insert, M 3/8" made from GFP	FS00Z39A00
– Connection hose DN 8, 1.5 m, with ball valve, FLEX Insert 90° ellbow made from GFP, cap nut FM 3/8"	
– Connector straight, FLEX Insert x M 3/8" made from GFP	
– Reduction FM 3/4" x M 3/8" made from GFP	

Manufacturer:  
**BWT water + more GmbH**  
 Walter-Simmer-Str. 4 · A-5310 Mondsee  
 Telefon +43 6232 5011-1164

Sales:  
**BWT water+more Deutschland:** info@water-and-more.de · Tel.: +49 611 58019-0  
**BWT water + more Austria:** kundenservice.wm@bwt-group.com · Tel.: +43 6232 5011-1164  
**BWT Aqua AG Schweiz:** info@bwt-aqua.ch · Tel.: +41 61 755 88 99  
**BWT UK Ltd:** WaterandMore@bwt-uk.co.uk · Tel.: +44 1494 838128

[www.bwt-wam.com](http://www.bwt-wam.com)

  
**BWT**  
 water + more